

TOPEX/Poseidon MGDR Quality Assessment Report

Cycle 383

05-02-2003 15-02-2003

Prepared by:	C. Schgounn, CLS	
	G. Pontonnier, CLS	
	M. Ablain, CLS	
Accepted by :	J. Dorandeu, CLS	
Quality visa:	M. Destouesse, CLS	
Approved by :	N. Picot, CNES	









1 Introduction. Document overview

The purpose of this document is to report the major features of the data quality from the Topex/Poseidon mission. The document is associated with data dissemination on a cycle by cycle basis.

The objectives of this document are:

To provide a data quality assessment

To provide users with necessary information for data processing

To report any change likely to impact data quality at any level, from instrument status to software configuration

To present the major useful results for the current cycle

It is divided into the following topics:

Cycle overview CALVAL main results

Cycle overview 2

2.1 Cycle quality and performances


Data quality for this cycle appears to be nominal. For this cycle, the crossover standard deviation is 5.88 cm rms, and the standard deviation of Sea Level Anomalies (SLA) relative to a Mean Sea Surface is 10.94 cm.

2.2 Warnings and recommendations

- Tape recorder failures :
 - There are a lot of data gaps due to tape recorder anomalies, especially in the Indian Ocean.
- Editing measurements (a): Problems in the interpolation of the TMR parameters occur when there are missing measurements (tape recorder failures). As a result 4.51% of the measurements are removed by the TMR correction criterion.
- Editing measurements (b): A new criterion has been added to the editing procedure since cycle 376 (See Editing). The mesurements removed by this criterion for the current cycle are plotted on the following figure.

T/P Cycle 383 (05/02/2003 / 15/02/2003) 30

Edited parameter: Radiometer and ECMWF wet tropospheric differences



3 CALVAL main results


This section presents results that illustrate data quality during this cycle. These verification products are produced operationally so that they allow systematic monitoring of the main relevant parameters.

3.1 Missing measurements


705790 altimeter measurements are present, and 88682 are missing.

The map below shows all the available measurements for this cycle and illustrates the tape recorder problems. The latter figure shows missing 1Hz measurements in the GDRs, with respect to a 1 Hz sampling of a nominal repeat track.

Available measurements TOPEX Cycle 383 (05/02/2003 / 15/02/2003)



TOPEX/Poseidon Cycle 383 (05/02/2003 / 15/02/2003)




TOPEX/Poseidon GDR Quality Assessment Report Cycle 383 05-02-2003 15-02-2003 SALP-RP-P2-EX-21072-CLS383

3.2 M-GDR quality flags


The following table indicates the percentage of measurements for which those flags are set.


Name	Descrition	% bad
Geo_Bad_1	altimeter land flag	26.72
Geo_Bad_1	ice flag	3.00
Geo_Bad_1	radiometer land flag	28.81
Alt_Bad_1	conditions 1 altimeter	4.06
Alt_Bad_2	conditions 2 altimeter	3.95
Geo_Bad_2	rain (liquid water in excess)	7.07
Geo_Bad_2	less than 4 points for CSR3.0 tide calculation	0.35
Geo_Bad_2	less than 4 points for FES95.2.1 tide calculation	2.26
TOPEX	TOPEX not valid	0.00
TMR	TMR not valid	0.00
TMR_Bad	Brightness temperatures not valid	5.23
DORIS	DORIS not valid	0.00


3.3 M-GDR parameter plots




TOPEX/Poseidon GDR Quality Assessment Report Cycle 383 05-02-2003 15-02-2003 SALP-RP-P2-EX-21072-CLS383



























3.4 Editing

The following table gives for each tested parameter, minimum and maximum thresholds, the number and the percentage of points removed.


As a comparison, the mean percentage over one year (1997) is also given.

There are problems in the interpolation of the TMR parameters since cycle 371 when there are missing measurements (tape recorder failures). These bad measurements are removed by the TMR correction criterion but some of them have been kept. Thus a new criterion has been added in the editing procedure since cycle 376 to remove all measurements for which the difference between the TMR and the ECMWF wet tropospheric corrections is greater than 20 cm. Even after applying this editing procedure, some anomalous TMR correction values remain (See wet tropo correction section).


Parameters	Min	Max	Unit	Mean %	% removed
	Thres.	Thres.		removed in	
				1997	
Sea surface height	-130.000	100.000	m	1.37	0.38
Number of 20/10Hz valid points Po-	5.000	-		1.37	0.55
seidon/TOPEX					
Std. deviation of range	0.000	0.100	m	1.85	1.31
Off nadir angle from waveform	0.000	0.400	deg	1.36	3.56
Dry tropospheric correction	-2.500	-1.900	m	0.00	0.00
Invert barometer correction	-2.000	2.000	m	0.00	0.00
TMR wet tropospheric correction	-0.500	-0.001	m	0.34	4.51
Ionospheric correction (Posei-	-0.400	0.040	m	0.00	0.00
don:Doris, TOPEX:Dual)					
Significant wave height	0.000	11.000	m	1.46	0.33
Sea state Bias	-0.500	0.000	m	1.39	0.42
Backscatter coefficient	7.000	30.000	dB	1.44	0.39
Ocean tide height	-5.000	5.000	m	0.01	0.47
Earth tide	-1.000	1.000	m	0.00	0.00
Pole tide	-15.000	15.000	m	0.00	0.00
TMR and ECMWF tropospheric	-0.200	0.200	m	NaN	0.57
differences					
Spline fitting					0.01

The following three maps are complementary: they show respectively the removed, the selected measurements and the percentage of selected measurements in the editing procedure.


Valid data TOPEX/Poseidon Cycle 383 (05/02/2003 / 15/02/2003)




Edited measurements
TOPEX Cycle 383 (05/02/2003 / 15/02/2003)





Percentage of valid data relative to the nominal pass TOPEX/Poseidon Cycle 383 (05/02/2003 / 15/02/2003)





3.5 Ionospheric correction
















3.6 Wet tropospheric corection




3.7 Crossover statistics

TPTP - CROSSOVER STATISTICS



SSH = Corrected sea surface height	SSH with FES95 tide model instead of GOT99		
SSH without dry thopospheric correction	SSH with CSR3 tide model instead of GOT99		
SSH without inverse barometer correction	SSH without BM4 SSB correction		
SSH without wet topospheric correction	SSH with BM3 SSB correction instead of BM4 SSB correction		
SSH with ECMWF tropo instead of TMR tropo	SSH without solid earth tide correction		
SSH without ionospheric correction filtered	SSH without polar tide correction		
SSH with DORIS iono correction instead of iono filtered	SSH = Corrected sea surface height with CNES orbit		
SSH without GOT99 tide model			

TPTP - CROSSOVER STATISTICS Without orbit error correction SSH = Corrected sea surface height RAPPEL DES SELECTIONS Type de points de croisement: TPTP Zone geographique (deg): -90 / 90, 0 / 360400 Seuil sur les ecarts d'analyse Selection(s) sur les champs : CL Arc 1 :=INTERP_SPLN CL Arc 2 :=INTERP_SPLN Seuil Min +: 0.0000000 Seuil Max : 0.0000000 300 Selection(s) sur les ecarts : 200 **RESULTATS STATISTIQUES** Valeur minimale : -29.6200 100 Valeur maximale : Difference Max - Min: 59.3900 Nombre de points lus: Nombre de points selectionnes: 5261 Moyenne: 0.354355 Ecart-type: 5.96914 Moyenne Quadratique : 5.97965 CLS Space Oceanography Division



TPTP - CROSSOVER STATISTICS SSH, BATHY < -1000 m, VAR OCE < 20 cm, LAT [-50°,+50] SSH = Corrected sea surface height before orbit error 190

RAPPEL DES SELECTIONS

Type de points de croisement: TPTP Zone geographique (deg): -50 / 50, 0 / 360

Seuil sur les ecarts d'analyse : aucun Selection(s) sur les champs :

CL Arc 1 :=BATHY
CL Arc 2 :=BATHY
Seuil Min : aucun
Seuil Max : -100000.00

CL Arc 1 := VAR_OCE CL Arc 2 := VAR_OCE Seuil Min : aucun Seuil Max : 20.000000 [...]

Selection(s) sur les ecarts : Aucune


RESULTATS STATISTIQUES

Valeur minimale : -25.0200 Valeur maximale : Difference Max - Min: 62.7500 Nombre de points lus: Nombre de points selectionnes: 2405

Moyenne: -0.0148400 Ecart-type : 5.42441

Moyenne Quadratique : 5.42443


CLS Space Oceanography Division




3.8 SSH variability

3.8.1 Sea Level Anomaly


TOPEX/Poseidon, cycle 383 Period : 05/02/2003 - 15/02/2003



TOPEX/Poseidon, cycle 383 Period : 05/02/2003 - 15/02/2003





TOPEX/Poseidon, cycle 383




3.8.2 Comparison to a precise Mean Sea Surface

The CLS (2001) MSS model is used as a reference to compute SLA. The two following maps respectively show the map of Topex SLA relative to the MSS and differences higher than a 30 cm threshold (after centering the data). The latter figure shows that higher differences are located in high ocean variability areas, as expected.






(SSH – MSS) differences greater than 0.3 m TOPEX/Poseidon Cycle 383 (05/02/2003 / 15/02/2003)



3.9 Dynamic topography

TOPEX/Poseidon, cycle 383


Period: 05/02/2003 - 15/02/2003



3.10 Wind and wave maps

These two figures show wind and wave estimations derived from 10 days of altimeter measurements.

TOPEX/Poseidon, cycle 383 Period: 05/02/2003 - 15/02/2003



Period: 05/02/2003 - 15/02/2003

