

TOPEX/Poseidon MGDR Quality Assessment Report

Cycle 397

24-06-2003 04-07-2003

Prepared by:	C. Schgounn, CLS	
	G. Pontonnier, CLS	
	M. Ablain, CLS	
Accepted by:	J. Dorandeu, CLS	
Quality visa :	M. Destouesse, CLS	
Approved by :	N. Picot, CNES	









1 Introduction. Document overview

The purpose of this document is to report the major features of the data quality from the Topex/Poseidon mission. The document is associated with data dissemination on a cycle by cycle basis.

The objectives of this document are:

To provide a data quality assessment

To provide users with necessary information for data processing

To report any change likely to impact data quality at any level, from instrument status to software configuration

To present the major useful results for the current cycle

It is divided into the following topics:

Cycle overview CALVAL main results

Cycle overview 2


2.1 Cycle quality and performances

Data quality for this cycle appears to be nominal. For this cycle, the crossover standard deviation is 6.58 cm rms, and the standard deviation of Sea Level Anomalies (SLA) relative to a Mean Sea Surface is 9.43 cm.

2.2 Warnings and recommendations

- Missing measurements :
 - There is a lot of data gaps due to tape recorder anomalies, especially in the Indian Ocean and in the Pacific Ocean close to the South America coasts.
- Doris ionospheric correction :
 - The DORIS instrument experienced an incident on 30, June 2003. Therefore there is no DORIS data available from 30/06/2003 to 01/07/2003. Only bent ionospheric correction is available during this period, that is from pass 136 to 237.
- Measurements edited by the TMR parameters : The following anomalies are explained by the problems in the interpolation of the TMR parameters due to tape recorder failures:
 - 2.18% of the measurements are removed by the TMR correction criterion (see the following figure).
 - Some measurements have radiometer land flag unset over land. A new criterion has been added to the editing procedure to remove all these measurements (see Editing)

Edited parameter: Radiometer wet tropospheric correction T/P Cycle 397 (24/06/2003 / 04/07/2003)




3 CALVAL main results


This section presents results that illustrate data quality during this cycle. These verification products are produced operationally so that they allow systematic monitoring of the main relevant parameters.

3.1 Missing measurements


696480 altimeter measurements are present, and 98060 are missing.

The map below shows all the available measurements for this cycle and illustrates the tape recorder problems. The latter figure shows missing 1Hz measurements in the GDRs, with respect to a 1 Hz sampling of a nominal repeat track.





Missing measurements TOPEX/Poseidon Cycle 397 (24/06/2003 / 04/07/2003)




TOPEX/Poseidon GDR Quality Assessment Report Cycle 397 24-06-2003 04-07-2003 SALP-RP-P2-EX-21072-CLS397

3.2 M-GDR quality flags


The following table indicates the percentage of measurements for which those flags are set.


Name	Descrition	% bad
Geo_Bad_1	altimeter land flag	25.69
Geo_Bad_1	ice flag	7.90
Geo_Bad_1	radiometer land flag	26.95
Alt_Bad_1	conditions 1 altimeter	5.73
Alt_Bad_2	conditions 2 altimeter	5.62
Geo_Bad_2	rain (liquid water in excess)	4.78
Geo_Bad_2	less than 4 points for CSR3.0 tide calculation	0.39
Geo_Bad_2	less than 4 points for FES95.2.1 tide calculation	2.89
TOPEX	TOPEX not valid	0.00
TMR	TMR not valid	0.00
TMR_Bad	Brightness temperatures not valid	5.25
DORIS	DORIS not valid	0.00


3.3 M-GDR parameter plots




TOPEX/Poseidon GDR Quality Assessment Report Cycle 397 24-06-2003 04-07-2003 SALP-RP-P2-EX-21072-CLS397



























3.4 Editing

The following table gives for each tested parameter, minimum and maximum thresholds, the number and the percentage of points removed. As a comparison, the mean percentage over one year (1997) is also given.

There are problems in the interpolation of the TMR parameters since cycle 371 when there are missing measurements (tape recorder failures). These bad measurements are removed by the TMR correction criterion but some of them have been kept. Thus a new criterion has been added to the editing procedure since the cycle 376 to remove all the mesurements where the absolute value of the difference between the TMR correction and the ECMWF model wet tropospheric correction is greater than 20 cm.


Probably due to the interpolation problem with the TMR, some measurements have radiometer land flag unset over land. This has no impact on the valid data because these measurements have been edited by the altimetric parameter criteria. Nevertheless, this anomaly leads to wrong statistics of the edited measurements. Therefore a new criterion has been added to the editing procedure to remove all the measurements for which the radiometer land flag is set to ocean and the altimeter land flag is set to land.

The number and percentage of points removed by each criterion is given on the following table. Note that these statistics are obtained with measurements already edited for radiometer land flag (26.95 % of points removed) and ice flag (7.90 % of points removed).


Parameters	Min	Max	Unit	Mean %	% removed
	Thres.	Thres.		removed in	
				1997	
Sea surface height	-130.000	100.000	m	1.37	0.18
Number of 20/10Hz valid points Po-	5.000	-		1.37	0.28
seidon/TOPEX					
Std. deviation of range	0.000	0.100	m	1.85	1.05
Off nadir angle from waveform	0.000	0.400	deg	1.36	3.88
Dry tropospheric correction	-2.500	-1.900	m	0.00	0.00
Invert barometer correction	-2.000	2.000	m	0.00	0.00
TMR wet tropospheric correction	-0.500	-0.001	m	0.34	2.18
Ionospheric correction (Posei-	-0.400	0.040	m	0.00	0.00
don:Doris, TOPEX:Dual)					
Significant wave height	0.000	11.000	m	1.46	0.10
Sea state Bias	-0.500	0.000	m	1.39	0.19
Backscatter coefficient	7.000	30.000	dB	1.44	0.18
Ocean tide height	-5.000	5.000	m	0.01	0.16
Earth tide	-1.000	1.000	m	0.00	0.00
Pole tide	-15.000	15.000	m	0.00	0.00
TMR and ECMWF tropospheric	-0.200	0.200	m	NaN	0.21
differences					
Spline fitting					0.01

The following three maps are complementary: they show respectively the removed, the selected measurements and the percentage of selected measurements in the editing procedure.


Valid data TOPEX/Poseidon Cycle 397 (24/06/2003 / 04/07/2003)




Edited measurements TOPEX Cycle 397 (24/06/2003 / 04/07/2003)





Percentage of valid data relative to the nominal pass TOPEX/Poseidon Cycle 397 (24/06/2003 / 04/07/2003)





3.5 Ionospheric correction
















3.6 Wet tropospheric corection



3.7 Crossover statistics





SSH = Corrected sea surface height SSH with FES99 tide model instead of GOT99 SSH = Corrected sea surface height with orbit error SSH with FES02 tide model instead of GOT99 SSH without dry thopospheric correction SSH with CSR3 tide model instead of GOT99 SSH without inverse barometer correction SSH with GOT002 tide model instead of GOT99 SSH without wet topospheric correction SSH without BM4 SSB correction SSH with corrected tropo instead of TMR tropo SSH with no-parametric SSB correction instead of BM4 SSB correction SSH with ECMWF tropo instead of TMR tropo SSH with BM3 SSB correction instead of BM4 SSB correction SSH without ionospheric correction filtered SSH without solid earth tide correction SSH with DORIS iono correction instead of iono filtered SSH without polar tide correction SSH without GOT99 tide model SSH = Corrected sea surface height with CNES orbit SSH with FES95 tide model instead of GOT99

T1T1 - CROSSOVER STATISTICS Without orbit error correction SSH = Corrected sea surface height RAPPEL DES SELECTIONS Type de points de croisement: T1T1

Selection(s) sur les champs : CL Arc 1 :=INTERP_SPLN CL Arc 2 :=INTERP_SPLN Seuil Min +: 0.000000 Seuil Max : 0.000000

Seuil sur les ecarts d'analyse

Zone geographique (deg): -90 / 90, 0 / 360

Selection(s) sur les ecarts :

Aucune


RESULTATS STATISTIQUES

Valeur minimale: -29.4000
Valeur maximale: 29.8900
Difference Max - Min: 59.2900
Nombre de points lus: 4879
Nombre de points selectionnes: 4771

Moyenne : 0.560042 Ecart-type : 6.64359

Moyenne Quadratique : 6.66715

CLS Space Oceanography Division



T1T1 – CROSSOVER STATISTICS With orbit error correction SSH = Corrected sea surface height

RAPPEL DES SELECTIONS

Type de points de croisement: T1T1

Zone geographique (deg): –90 / 90 , 0 / 360 Seuil sur les ecarts d'analyse

Selection(s) sur les champs : CL Arc 1 :=INTERP_SPLN CL Arc 2 :=INTERP_SPLN Seuil Min +: 0.0000000 Seuil Max : 0.0000000

Selection(s) sur les ecarts :

Aucune

RESULTATS STATISTIQUES

-28 0800

Valeur maximale : 29.7600

Difference Max – Min: 57.8400

Nombre de points lus: 4879


Nombre de points selectionnes: 4748

Moyenne : 0.107885 Ecart-type : 5.85089

Valeur minimale:

Moyenne Quadratique : 5.85189

CLS Space Oceanography Division



T1T1 - CROSSOVER STATISTICS SSH, BATHY < -1000 m, VAR OCE < 20 cm, LAT [-50 $^{\circ}$,+50] SSH = Corrected sea surface height before orbit error **RAPPEL DES SELECTIONS** Type de points de croisement: T1T1 Zone geographique (deg): -50 / 50, 0 / 360190 Seuil sur les ecarts d'analyse : aucun 180 Selection(s) sur les champs : CL Arc 1 :=BATHY CL Arc 2 :=BATHY Seuil Min : aucun Seuil Max : -100000.00 160 150 CL Arc 1 := VAR_OCE CL Arc 2 := VAR_OCE Seuil Min : aucun Seuil Max : 20.000000 140 130 Selection(s) sur les ecarts : 120 110 100

RESULTATS STATISTIQUES

Valeur minimale : -26.6400 Valeur maximale : Difference Max - Min: 64.6000 Nombre de points lus: Nombre de points selectionnes: 2406


Moyenne: 0.0231260 Ecart-type : 5.80304

[...]

Aucune

Moyenne Quadratique : 5.80309


CLS Space Oceanography Division




3.8 SSH variability

3.8.1 Sea Level Anomaly


TOPEX/Poseidon, cycle 397 Period : 24/06/2003 – 04/07/2003



TOPEX/Poseidon, cycle 397 Period : 24/06/2003 – 04/07/2003




TOPEX/Poseidon, cycle 397 Period : 24/06/2003 – 04/07/2003




3.8.2 Comparison to a precise Mean Sea Surface

The CLS (2001) MSS model is used as a reference to compute SLA. The two following maps respectively show the map of Topex SLA relative to the MSS and differences higher than a 30 cm threshold (after centering the data). The latter figure shows that higher differences are located in high ocean variability areas, as expected.






(SSH – MSS) differences greater than 0.3 m TOPEX/Poseidon Cycle 397 (24/06/2003 / 04/07/2003)



3.9 Dynamic topography


TOPEX/Poseidon, cycle 397 Period : 24/06/2003 – 04/07/2003



3.10 Wind and wave maps

These two figures show wind and wave estimations derived from 10 days of altimeter measurements.

TOPEX/Poseidon, cycle 397 Period : 24/06/2003 – 04/07/2003



Wind Speed (m/s)
TOPEX/Poseidon, cycle 397
Period: 24/06/2003 - 04/07/2003

